

SKIL The Power To Perform

**Short removal time.
Long tool life.**



www.skil-up.com



Skil 3 000 6" Bench Grinder



- Vented bonded R80 and F80, Type 1 grinding wheels with aluminum oxide and silicon carbide grains for long service life and fast removal rate
- Die-cast housing to keep the motor free of dust
- Robust and sturdy die-cast base provides extra steadiness
- Large and adjustable work fields
- Spark protective guards made of steel for extra safety
- Dust-proof on/off switch for protection against short circuits
- Adjustable work piece support for easy handling while grinding or sharpening

Specifications

Country version	China, Hong Kong, Thailand, Vietnam	Saudi Arabia, The Philippines	India, Indonesia, Singapore	Malaysia
Input power	370 W	370 W	300 W	290 W
Voltage	220 V	220 V	220V	240 V
Frequency	50 Hz	50Hz	50 Hz	50Hz
No. & cut speed	2800 rpm	3000 rpm	2800 rpm	2800 rpm
Wheel diameter	150 mm	150 mm	150 mm	150 mm
Wheel thickness	20 mm	20 mm	20 mm	20 mm
Advance	12.7 mm	12.7 mm	12.7 mm	12.7 mm
Weight	10.2 kg	10.2 kg	10.2 kg	10.2 kg
Production year	1	1	1	1



High performance motor developed to work for long hours



Large and adjustable work fields



Easy to use with a dust-proof on/off switch

Standard equipment

- Spark protective guard: 2 pieces
- Spark shields: 2 pieces
- 6" wheels (R80 & F80): 2 pieces (1 each)
- Disc flange: 2 pieces

